

BLANK PAGE



IS: 7532 - 1974 (Reaffirmed 2011)

Indian Standard SPECIFICATION FOR SOFT SOAP

(Fourth Reprint JANUARY 1997)

UDC 661.187.4

© Copyright 1973

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Gr 2 June 1975

AMENDMENT NO. 4 MARCH 2002 TO

IS 7532: 1974 SPECIFICATION FOR SOFT SOAP

[Page 5, clause 5.2(e)] — Insert the following new item at the end:

'f) Critical ingredients mentioning the actual compound in descending order up to a limit of 0.5 percent by mass, as identified under ECO-Mark Scheme.'

(CHD 25)						
	Reprography	Unit,	BIS,	New	Delhi,	India

AMENDMENT NO. 3 OCTOBER 1989 TO IS:7532-1974 SPECIFICATION FOR SOFT SOAP

(Page 4, clause 4.2) - Insert the following Note after 4.2:

'NOTE - The material shall be considered as showing no sign of deterioration if it still conforms to 4.1.'

(CDC 35)

Reprography Unit, BIS, New Delhi, India

AMENDMENT NO. 2 MARCH 1986 TO

IS:7532-1974 SPECIFICATION FOR SOFT SOAP

(pace 3, clause 0.3) - Substitute the following for the existing clause:

'0.3 Soft soap is intended for general washing and cleaning purposes and can be used as lubricant and coolant in machine operation/conveyor belts in the form of aqueous solution.'

(CDC 35)

Reprography Unit, BIS, New Delhi, India

AMENDMENT NO. 1 JANUARY 1985

TO

IS: 7532-1974 SPECIFICATION FOR SOFT SOAP

(Page 7, clause A-2.1, line 5) - Substitute 'blue' for 'pink'.

(CDC 35)

Reprography Unit BIS New Delhi, India

Indian Standard SPECIFICATION FOR SOFT SOAP

Soaps and Other Surface Active Agents Sectional Committee, CDC 35

Chairman

Representing

DR B. P. GODREJ

Codrej Soaps Pvt Ltd, Bombay; and Indian Chemical Manufacturers' Association, Calcutta

Members

SHRI M. S. THAKER (Alternate to

Dr B. P. Godrej)

SHRI M. A. BHATT

SHRI A. K. BHATTACHARYA

SHRI N. BHOWMIK

SHRI O. P. SAXENA (Alternate)

DR D. R. DHINGRA

SHRI K. S KRISHNAN (Alternate)
SHRI M. L DHIR

SHRIM. L DHIK

SHRI P. N. AGARWAL (Alternate)

SHRI S. C. GHOSE

DR C. S. HATTIANODI

SHRI V. LAKSHMIKANTHAN

SHRIS. M. MISTRY

SHRI M. S. MHAISKAK (Alternate)

DR N. L. MURTHY

SHRIT. S. RAMASWAMY (Alternate)

SHRI S. C. PANDE

SHRI V. S. RAMANATHAN

SHRI P. P. MATHEW (Alternate)

SHRI S. SUBBIAH

SHRI N. G S IYER (Alternate)

SHRI B. K. ???

SHRI V. JAYAPPA (Alternate)

DR O. M. SAXENA, Director (Chem) Chemical Manufacturers' Associat

Swastik Household & Industrial Products Pvt Ltd

Bombay National Tost House, Calcutta

Directorate General of Technical Development,

New Delhi

Oil Technologists' Association of India, Kanpur

Ministry of Defence (DGI)

Indian Soap and Toiletries Makers' Association,

Calcutta

Hindustan Lever Ltd, Bombay

Khadi & Village Industries Commission, Bombay

Ahura Chemical Products Pvt Ltd, Bombay

Tata Oil Mills Co Ltd, Bombay

Development Commissioner, Small Scale Industries, New Delhi

Central Board of Revenues, Ministry of Vinance, New Delhi

Directorate General of Supplies & Disposals,

New Delhi

Governiment Soap Factory, Bangalore

Director General, BIS (Ex-officio Member)

Secretary

SHRI R. K. SINGH Assistant Director (Chem), BIS

(Continued on page 2)

© Copyright 1975

BUREAU OF INDIAN STANDARDS

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 7532 - 1974

(Continued from page 1)

Soap Subcommittee, CDC 35:1

Convener

Representing

DR G. S. HATTIANGDI

Hindustan Lever Ltd, Bombay

Members

DR S. M. PATEL (Alternate to

Dr G. S. Hattiangdi)

SHRI M. A. BHATT

Swastik Household & Industrial Products Pvt Ltd, Bombay

SHRI R. B. BAROT (Alternate)

SHRI M. L. ??? DR B. P. GODREJ

SHRI M. S. THAKUR (Alternate)

SHRIS. G. DAS GUPTA

SHRIK. S. KRISHNAN

SHRI V. LAKSHMIKANTHAN

SHRIT. S. RAMASWAMY
DR A. S SHITOLE (Alternate)

SHRI M. L. SAHOO

DR ASHIM GUPTA (Alternate)

SHRI B. K. ???

SHRI V. JAYAPPA (Alternate)

Ministry of Defence (DGI)

Godrej Soaps Pvt Ltd, Bombay

The Calcutta Chemical Co Ltd, Calcutta Oil Technologists' Association of India, Kanpur Khadi & Village Industries Commission, Bombay Tata Oil Mills Co Ltd, Bombay

Kusum Products Ltd, Calcutta

Government Soap Factory, Bangalore

Panel to Review Indian Standards on Soaps, CDC 35:1:1

Convener

DR G. S. HATTIANG???

Hindustan Lever Ltd, Bombay

Members

SHRI N. BHOWMIK

New Delhi

SHRI M. L. DHIR SHRI I. A. MEHTA Ministry of Defence (DGI) Swastik Household & Industrial Products Pvt Ltd,

Small

Scale

Directorate General of Technical Development,

Bombay

DR N. L. MURTHY

Tata Oil Mills Co Ltd, Bombay

SHRI T. S. RAMASWAMY (Alternate)
SHRI S. C. PANDE De

Development Commissioner,

Industries, New Delhi

SHRIM. S. THAKUR

Godrej Soaps Pvt Ltd, Bombay

Indian Standard

SPECIFICATION TOR SOFT SOAP

0. FOREWORD

- **0.1** This Indian Standard was adopted by the Indian Standards Institution on 25 November 1974, after the draft finalized by the Soaps and Other Surface Active Agents Sectional Committee had been approved by the Chemical Division Council.
- **0.2** Soft soap is distinguished from ordinary hard soap by its soft, jelly-like texture and thus is usually packed in metal or waxed paper containers.
- **0.3** Soft soap is intended for general washing and cleaning purposes and for industrial purposes in the form of aqueous solution.
- **0.4** In the preparation of this standard, assistance has been derived from the following publications which is thankfully acknowledged:
 - i) G/O. P. 61E-1960 Soft soap. Directorate General of Supplies & Disposals, Government of India.
 - ii) BS 1913: 1966 Soft soap. British Standards Institution.
- **0.5** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes requirements and methods of sampling and test for soft soap.

2. TERMINOLOGY

2.1 For the purpose of this standard, the definitions given in 2 of IS: 286-1966† shall apply.

3. TYPES

- 3.1 The material shall be of following two types:
 - a) Type 1, and
 - b) Type 2.

^{*}Rules for rounding off numerical values (revised).

[†]Methods of sampling and test for soaps (first revision).

4. REQUIREMENTS

- **4.1 Description** The material shall be homogeneous translucent mass of jelly-like texture, free from putrescent, fishy or objectionable odour. It applies to soft soap with potassium or sodium base or a mixture of these bases. It does not apply to soaps for medicinal purposes. It may or may not be suitably perfumed subject to agreement between the purchaser and the supplier. It shall be free from foreign matter and visible impurities.
- **4.2** The material shall quickly form a satisfactory lather while in use and shall show no sign of any deterioration on storage in original sealed containers under normal conditions for a period of 12 months.
- **4.3** Consistency The soap shall not become liquid at 32°C, and no liquid shall separate when the soap is maintained at 0°C, for 24 hours.
- **4.4 Calculation of Results** Soft soap is liable to lose moisture on keeping. The results obtained for unsaponified and unsaponifiable matter, total free alkali and free caustic alkali by the specific methods of analysis shall, therefore, be recalculated in relation to the specified minimum total fatty matter by means of the equation:

Recalculated result = Actual result × Minimum specified total fatty matter

Actual total fatty matter

TARLE 1 DECILIDEMENTS FOR SOFT SOAP

4.5 The material shall comply with the requirements given in Table 1.

(Clauses 4.5 and 7.1)						
SL No.	CHARACTERISTIC	REQUIREMENT		METHOD OF TEST, REF TO		
	•	Type 1	Type 2	Cl No. in IS: 286-1966*	Appendix	
(1)	(2)	(3)	(4)	(5)	(6)	
i)	Total fatty matter, percent by mass, Min	38	28	15 –		
ii)	Unsaponified and unsaponifiable matter, percent by mass, Max	2.5	2.0	12		
iii)	Rosin acids, percent by mass of total fatty matter, Max	Nil	15.0	14	_	
iv)	Total free alkali (as K ₂ O), percent by mass, Max	0.50	0.50	-	A	
v)	Free caustic alkali (as K ₂ O),	0.10	0.10	6	_	
	percent by mass, Max			(see Note below	v)	
	NOTE — Modify the formula gi	ven in 6 of	IS: 286-1966	* as given belo	w:	
				VN		

Free caustic alkali (as K_2O), percent by mass = 4.7 $\frac{N}{M}$

where

 $V=\mbox{volume}$ in ml of standard sulphuric $% \mbox{acid}$ or hydrochloric acid used, N= normality of the acid, and

M =mass in g of the material taken for test.

^{*}Methods of sampling and test for soaps (first revision).

5. PACKING AND MARKING

- **5.1 Packing** The material shall be supplied in suitable containers as agreed to between the purchaser and the supplier.
- **5.2 Marking** The packages shall be securely closed and marked with the following particulars:
 - a) Name of manufacturer;
 - Type and brand name of the material and recognized trade-mark, if any;
 - c) Year and month of manufacture;
 - d) Net mass when packed; and
 - e) Batch No. or Lot No. in code or otherwise.

5.3 BIS Certification Marking

The product may also be marked with Standard Mark.

5.3.1 The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The details of conditions under which the licence for the use of Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

6. SAMPLING

6.1 For this purpose general precautions, scale of sampling and preparation of test samples, shall be as prescribed in **3.1**, **3.2** and **3.3** respectively of IS: 286-1906*.

6.2 Number of Tests

- **6.2.1** Tests for the determination of characteristics given at Sl No. (i), (ii), and (v) in Table 1 shall be conducted on each of the individual samples separately.
- **6.2.2** Tests for determination of all the remaining characteristics shall be conducted on the composite sample.

6.3 Criteria for Conformity

6.3.1 For Individual Samples — For each of the characteristics which have been determined on the individual samples (6.2.1) the mean (x) and the range (R) of the test results shall be calculated as follows:

Mean
$$(x) = \frac{\text{the sum of test results}}{\text{number of test results}}$$

^{*}Methods of sampling and test for soaps (first revision).

IS: 7532 - 1974

Range (R) - The difference between the maximum and the minimum value of the test results.

The lot shall be deemed as conforming to the requirement if the expression ($\bar{x} - 0.4 R$) is greater than or equal to minimum value given in Table 1 and ($\bar{x} + 0.4 R$) is less than or equal to maximum value given in Table 1.

6.3.2 For Composite Sample — For declaring the conformity of the lot to the requirements of other characteristics determined on the composite sample, the test results for each of the characteristics shall satisfy the relevant requirement.

7. TESTS

- **7.1** Tests shall be conducted as prescribed in IS: 286-1966* and in Appendix A. Reference to the relevant clauses of that standard and Appendix A is given in col 5 and 6 of Table 1 respectively.
- 7.2 Quality of Reagents Unless specified otherwise, pure chemicals and distilled water (see IS: 1070-1960†) shall be employed in tests.

NOTE — 'Pure chemicals' shall mean chemicals that do not contain impurities which affect the results of analysis.

APPENDIX A

[Table 1, Sl No.(iv)]

DETERMINATION OF TOTAL FREE ALKALI

A-1. REAGENTS

- A-1.1 Ethanol 95 percent (v/v).
- A-1.2 Ethanolic Potassium Hydroxide Solution 0.1 N.
- A-1.3 Standard Sodium Hydroxide Solution 1 N.
- A-1.4 Standard Sulphuric Acid 1 N.
- A-1.5 Thymolphthalein Indicator 0.1 percent in 60 percent ethanol.

A-2. PROCEDURE

A-2.1 Boil 100 ml of ethanol in a 400-ml flask under reflux, add 1 ml of thymolphthalein indicator, allow to cool to 70°C and neutralize at that temperature with ethanolic potassium hydroxide solution. Add 10 g of the

^{*}Methods for sampling and test tor soaps (first revision).

[†]Specification for water, distilled quality (revised).

IS:7532-1974

Range (R) - The difference between the maximum and the minimum value of the test results.

The lot shall he deemed as conforming to the requirement if the expression ($\ddot{x} \sim 0.4 R$) is greater than or equal to minimum value given in Table 1 and ($\ddot{x} + 0.4 R$) is less than or equal to maximum value given in Table 1.

the the rw

7. 7. A' A

di

A-1.3 Standard Sodium Hydroxide Solution - 1N

A-1.4 Standard Sulphuric Acid - 1 N.

A-1.5 Thymolphthalein Indicator - 0.1 percent in 60 percent ethanol.

A-2 PROCEDURE

A-2.1 Boil 100 ml of ethanol in a 400-ml flask under reflux, add 1 ml of thymolphthalein indicator, allow to cool to 70°C and neutralize at that temperature with ethanolic potassium hydroxide solution. Add 10 g of the

sample and dissolve it as quickly as possible by heating Immediately after complete solution of the soap, add 3 ml of standard sulphuric acid and boil on a water-bath for at least 10 minutes to ensure complete removal of carbon dioxide. If the solution is colourless, cool to 70 C and titrate with standard sodium hydroxide solution until the pink colour reappears. If alter boiling with acid the pink colour returns, add a further quantity of standard sulphuric acid and repeat the boiling, the titration being completed as above. The excess of standard sulphuric acid finally titrated shall be not less than 1 ml.

A-3. CALCULATION

A-3.1 Total free alkali (as K2O), percent by mass - $\frac{4.7 \left(V_1 - V_2 \right)}{M}$

where

 V_1 = volume in ml of standard sulphuric acid added,

 V_2 = volume in ml of standard sodium hydroxide solution required, and

M = mass in g of the sample taken for the test.

^{*}Methods for sampling and test for soaps (first revision).
†Specification for water, distilled quality (revised).

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 323 0131, 323 8375, 323 9402

Fax: 91 11 3234062, 91 11 3239399

Fax: 91 11 3234062, 91 11 3239399	
	Telegrams: Manaksanstha (Common to all Offices)
Central Laboratory;	Telephone
Plot No. 20/9, Site IV, Sahibabad Industrial Area, Sahibabad 201010	8-77 00 32
Regional Offices:	
Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 11	0002 323 76 17
*Eastern: 1/14 CIT Scheme VII M, V.I.P. Road, Maniktola, CALCUTTA	700054 337 86 62
Northern: SCO 335-336, Sector 34-A, CHANDIGARH 160022	60 38 43
Southern: C.I.T. Campus, IV Cross Road, CHENNAI 600113	235 23 15
†Western : Manakalaya, E9, Behind Marol Telephone Exchange, A MUMBA1 400093	ndheri (East), 832 92 95
Branch Offices::	
'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 38000	550 13 46
‡Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road, BANGALORE 560058	839 49 55
Gangotri Complex, 5th Floor, Bhadbhada Road, T.T. Nagar, BHOPAL	462003 55 40 21
Plot No. 62-63, Unit VI, Ganga Nagar, BHUBANESHWAR 751001	40 36 27
Kalaikathir Buildings, 670 Avinashi Road, COIMBATORE 641037	21 01 41
Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001	8 28 88 01
Savitri Complex, 116 G.T. Road, GHAZIABAD 201001	8-71 19 96
53/5 Ward No.29, R.G. Barua Road, 5th By-lane, GUWAHATI 781003	54 11 37
5-8-56C, L.N. Gupta Marg, Nampally Station Road, HYDERABAD 5000	20 10 83
E 52, Chitaranjan Marg, C-Scheme, JAIPUR 302001	37 29 25
117/41B B, Sarvodaya Nagar, KANPUR 208005	21 68 76
Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kis LUCKNOW 226001	shore Road, 23 89 23
Patliputra Industrial Estate, PATNA 800013	26 23 05
T.C. No. 14/1421, University P. O. Palayam, THIRUVANANTHAPURAM	A 695034 6 21 17
Inspection Offices (With Sale Point):	
Pushpanjali, 1st Floor, 205-A, West High Court Road, Shankar Na NAGPUR 440010	ngar Square, 52 51 71
Institution of Engineers (India) Building 1332 Shivaji Nagar, PUNE 4110	32 36 35
*Sales Office is at 5 Chowringhee Approach, P.O. Princep Street, CALCUTTA 700072	27 10 85
†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400007	309 65 28
‡Sales Office is at 'F' Block, Unity Building, Narashimaraja Square, BANGALORE 560002	222 39 71